



LED Downlight ND361E - ND364E

Features

- 15W / 24W / 32W / 41W LED Downlight
- Recessed round, uniform distribution
- Ideal replacement up to 70W HID downlight
- Special color spectrum for aquarium, agriculture and food display available on request
- Good color rendition, $R_a \geq 80$
- Dimmable as option

Materials / Finish

- Body: Die cast aluminium
- Trim: Die cast aluminium
- Reflector: High purity, anodized aluminium

Installation / Mounting



- Quick installation with mounting bracket
- Suitable for recessed mount
- Remote gear unit allows flexible and easy installation
- Cut out dimensions Ø90mm / Ø125mm / Ø170mm / Ø200mm



Standards

- Designed and manufactured to comply with international standard EN60598
- Class II Electrical
- IP 20

Dimming Options



(Unit : mm)	(D)	(H)	Cut Out Dimensions
ND361E	Ø105 x	90	Ø90
ND362E	Ø138 x	127	Ø125
ND363E	Ø190 x	148	Ø170
ND364E	Ø230 x	172	Ø200

Model	Voltage	Luminaire Wattage	Driver	Color Temp	Beam Angle	Luminaire Lumen	ENERGY
ND361E-15W/830	220 - 240V	15W	DC 36±2V C.C. 350mA	3000K	15° / 24° / 38°	1180lm	F
ND361E-15W/840	220 - 240V	15W	DC 36±2V C.C. 350mA	4000K	15° / 24° / 38°	1215lm	F
ND361E-15W/850	220 - 240V	15W	DC 36±2V C.C. 350mA	5000K	15° / 24° / 38°	1260lm	F
ND362E-24W/830	220 - 240V	24W	DC 36±2V C.C. 600mA	3000K	15° / 24° / 38°	2085lm	F
ND362E-24W/840	220 - 240V	24W	DC 36±2V C.C. 600mA	4000K	15° / 24° / 38°	2135lm	F
ND362E-24W/850	220 - 240V	24W	DC 36±2V C.C. 600mA	5000K	15° / 24° / 38°	2185lm	F
ND363E-32W/830	220 - 240V	32W	DC 36±2V C.C. 800mA	3000K	15° / 24° / 38°	2860lm	F
ND363E-32W/840	220 - 240V	32W	DC 36±2V C.C. 800mA	4000K	15° / 24° / 38°	2910lm	F
ND363E-32W/850	220 - 240V	32W	DC 36±2V C.C. 800mA	5000K	15° / 24° / 38°	2960lm	F
ND364E-41W/830	220 - 240V	41W	DC 36±2V C.C. 1050mA	3000K	15° / 24° / 38°	3735lm	F
ND364E-41W/840	220 - 240V	41W	DC 36±2V C.C. 1050mA	4000K	15° / 24° / 38°	3785lm	F
ND364E-41W/850	220 - 240V	41W	DC 36±2V C.C. 1050mA	5000K	15° / 24° / 38°	3830lm	F

