



LED Downlight ND401E - ND406E

Features

- 4W / 6W / 9W / 12W / 18W / 24W LED Downlight
- Recessed round, uniform distribution
- Comfort glare-free diffuser
- Ideal replacement up to 2x26W compact fluo. downlight
- Low profile and slim (only 26-30mm deep), suitable for shallow ceiling void
- Integral driver
- Good color rendition, Ra ≥80

Materials / Finish


- Body: Thermoplastic polypropylene (PP)
- Trim: Thermoplastic polypropylene (PP)
- Diffuser: Frosted PS, UV protected

Installation / Mounting


- Quick installation with mounting bracket
- Suitable for recessed mounting
- Integral gear unit allows quick and easy installation
- Cut out dimensions Ø78mm / Ø100mm / Ø125mm / Ø155mm / Ø190mm / Ø270mm

Standards

- Designed and manufactured to comply with international standard EN60598
- Class II Electrical
- IP 20



(Unit : mm)	(D)	(H)	Cut Out Dimensions
ND401E	Ø98	x 26	Ø78
ND402E	Ø118	x 26	Ø100
ND403E	Ø144	x 26	Ø125
ND404E	Ø177	x 26	Ø155
ND405E	Ø219	x 30	Ø190
ND406E	Ø299	x 30	Ø270



Model	Voltage	Luminaire Wattage	Color Temp	Beam Angle	Luminaire Lumen	
ND401E-4W/830	220 - 240V	4W	3000K	120°	305lm	F
ND401E-4W/840	220 - 240V	4W	4000K	120°	310lm	F
ND401E-4W/865	220 - 240V	4W	6500K	120°	315lm	F
ND402E-6W/830	220 - 240V	6W	3000K	120°	455lm	F
ND402E-6W/840	220 - 240V	6W	4000K	120°	465lm	F
ND402E-6W/865	220 - 240V	6W	6500K	120°	475lm	F
ND403E-9W/830	220 - 240V	9W	3000K	120°	685lm	F
ND403E-9W/840	220 - 240V	9W	4000K	120°	695lm	F
ND403E-9W/865	220 - 240V	9W	6500K	120°	705lm	F
ND404E-12W/830	220 - 240V	12W	3000K	120°	915lm	F
ND404E-12W/840	220 - 240V	12W	4000K	120°	980lm	F
ND404E-12W/865	220 - 240V	12W	6500K	120°	1045lm	F
ND405E-18W/830	220 - 240V	18W	3000K	120°	1370lm	F
ND405E-18W/840	220 - 240V	18W	4000K	120°	1420lm	F
ND405E-18W/865	220 - 240V	18W	6500K	120°	1465lm	F
ND406E-24W/830	220 - 240V	24W	3000K	120°	1825lm	F
ND406E-24W/840	220 - 240V	24W	4000K	120°	1865lm	F
ND406E-24W/865	220 - 240V	24W	6500K	120°	1900lm	F

