





LED PLT/E AC

Features


- Energy saving with low power consumption
- LED PLT/E 4PIN is not suitable for ECG Circuit. The ECG should be bypassed for AC connection
- For direct connection with AC
- Instant full brightness
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Full glass body
- Voltage: 220-240Vac, 50/60Hz, Power Factor: 0.5
- Good color rendition, Ra ≥80

	
10W	~ 32W
13W	~ 42W



EUROPE
CFLni


GX24q base



(Unit : mm)	(L)	(W)	(H)
10W	140	x 49	x 45
13W	165	x 49	x 45



Model	Voltage	Wattage	Base	Color Temp	Beam Angle	Type	Lumen	
LED PLTE/32-10W/AC/830/G/4P	220 - 240V	10W	GX24q	3000K	360°	AC	1300lm	E
LED PLTE/32-10W/AC/840/G/4P	220 - 240V	10W	GX24q	4000K	360°	AC	1350lm	D
LED PLTE/32-10W/AC/865/G/4P	220 - 240V	10W	GX24q	6500K	360°	AC	1400lm	D
LED PLTE/42-13W/AC/830/G/4P	220 - 240V	13W	GX24q	3000K	360°	AC	1760lm	D
LED PLTE/42-13W/AC/840/G/4P	220 - 240V	13W	GX24q	4000K	360°	AC	1805lm	D
LED PLTE/42-13W/AC/865/G/4P	220 - 240V	13W	GX24q	6500K	360°	AC	1850lm	D



Direct 220 - 240V AC input. Integral LED driver
This LED PLT/E is not suitable for ECG Circuit. Please bypass the ECG for AC connection