

LED PLT/E AC

10W/13W

Features


- Energy saving with low power consumption
- LED PLT/E 4PIN is not suitable for ECG Circuit. The ECG should be bypassed for AC connection
- For direct connection with AC
- Instant full brightness
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Full glass body
- Voltage : 220-240Vac, 50/60Hz, Power Factor: 0.5
- Good color rendition, Ra ≥80



Diagrams


Dimensions:

GX24q base



(Unit : mm)	(L)	(W)	(H)
10W	140	x 49	x 45
13W	165	x 49	x 45

Circuits:



Direct 220 - 240V AC input. Integral LED driver
This LED PLT/E is not suitable for ECG Circuit. Please bypass the ECG for AC connection

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



Applications



Home



Office



Shopping mall



Hotel



Supermarket



Restaurant



School



Hospital

Technical Data

Type of Light Source

Lighting Technology Used LED

Non-directional or Directional [NDLS/DLS] NDLS

Mains or Non-mains [MLS/NMLS] MLS

Connected Light Source No

Color tunable light source No

Envelop [No/Second/Non-Clear] No

High Luminance Light Source No

Anti-glare Shield No

Electrical

Rated Wattage [W] 10W / 13W

On-mode Power [W] 10W / 13W

Standby Power [W] N/A

Networked Standby Power [W] N/A

Rated Voltage [V/Hz] 220-240Vac, 50/60Hz

Power Factor @230V 0.5

Input Current [mA] @230V 87 / 113

Model

LED PLTE/32-10W/AC/8XX/G/4P 10W

LED PLTE/42-13W/AC/8XX/G/4P 13W

Luminous Flux (Useful Luminous Flux) [lm]

10W 1300lm @3000K

1350lm @4000K

1400lm @6500K

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

13W	1760lm @3000K
	1805lm @4000K
	1850lm @6500K
Performance	
SDCM	<6
Chromaticity coordinates [x, y]	0.44, 0.403@3000K / 0.38, 0.38@4000K / 0.312, 0.335@6500K
Efficacy [lm/W]	130-142
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	360
Rated Life, Ta@25°C [hrs]	30,000
Survival Factor	0.9
Lumen Maintenance Factor	0.96
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<1
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.7
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Length L [mm]	140 / 165
Width W [mm]	49
Height H [mm]	45
Base	GX24q
Material	Glass
Standard Compliance	
CE-LVD	EN62560
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	3000K / 4000K / 6500K
10W	E / D / D
13W	D / D / D
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C
Claim of Equivalent Power, 10W [W]	32W
Claim of Equivalent Power, 13W [W]	42W
Energy Consumption in on-mode [kWh/1000h]	10kWh / 13kWh