


LED Solar Floodlight UF171S-175S


Features

- Solar-powered and Eco-friendly with ZERO electricity cost
- Tempered glass solar panel and die-cast aluminium housing withstanding severe weather conditions
- Remote control to adjust operation time and brightness level
- Embedded with Daylight Sensor
- Plug and play power cord, easy installation
- Built-in Lithium iron phosphate battery, discharge time from 5-6 hours
- Good color rendition, Ra ≥80



Diagrams

Dimensions:



Solar Panel

(Unit: mm)	(L)	(L1)	(W)	(H)
UF171S	228 X	199 X	207 X	43
UF172S	274 X	231 X	251 X	43
UF173S	324 X	281 X	286 X	46
UF174S	369 X	326 X	326 X	51
UF1745S	415 X	371 X	396 X	51

(Unit: mm)	(L2)	(W1)
UF171S	235 X	350
UF172S	290 X	350
UF173S	450 X	350
UF174S	600 X	350
UF1745S	670 X	445

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



IP66

Applications



Parking



Garden

Technical Data

Electrical

Rated input	Powered by solar panel
-------------	------------------------

LED	SMD
-----	-----

Model - Luminous Flux(lm)

UF171S-8xx	300lm @3000K-6500K
------------	--------------------

UF172S-8xx	600lm @3000K-6500K
------------	--------------------

UF173S-8xx	890lm @3000K-6500K
------------	--------------------

UF174S-8xx	1440lm @3000K-6500K
------------	---------------------

UF175S-8xx	1700lm @3000K-6500K
------------	---------------------

Battery Capacity

UF171S-8xx	5AH 3.2V
------------	----------

UF172S-8xx	10AH 3.2V
------------	-----------

UF173S-8xx	15AH 3.2V
------------	-----------

UF174S-8xx	25AH 3.2V
------------	-----------

UF175S-8xx	30AH 3.2V
------------	-----------

Performance

SDCM	<6
------	----

Color Rendering Index [Ra]	≥80
----------------------------	-----

Beam Angle [°]	90
----------------	----

Rated Life, Ta@25°C [hrs]	20,000
---------------------------	--------

Discharge time [hrs]	5 - 6
----------------------	-------

Mechanical

Length L [mm]	228 / 274 / 324 / 369 / 415
---------------	-----------------------------

Width W [mm]	207 / 251 / 286 / 326 / 396
--------------	-----------------------------

Height H [mm]	43 / 43 / 46 / / 51 / 51
---------------	--------------------------

Material	Aluminium
----------	-----------

Standard Compliance

Mercury Content [mg]	
----------------------	--

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Other	
Dimmable [Y/N]	Y
Operation Temperature [°C]	-20°C ~ 45°C
Storage Temperature [°C]	-20°C ~ 45°C