



LED PLD/E AC

Features


- Energy saving with low power consumption
- LED PLD/E 4PIN is not suitable for ECG Circuit. The ECG should be bypassed for AC connection
- For direct connection with AC
- Instant full brightness
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Full glass body
- Voltage: 220-240Vac, 50/60Hz, Power Factor: 0.5
- Good color rendition, Ra ≥80

EUROPE


CFLni

LED	~	10W
4.5W	~	13W
5W	~	18W
6W	~	26W
9W	~	

G24q base




(Unit : mm)	(L)	(W)	(H)
4.5W	109	x 35	x 35
5W	143	x 35	x 35
6W	143	x 35	x 35
9W	168	x 35	x 35



Model	Voltage	Wattage	Base	Color Temp	Beam Angle	Type	Lumen	ENERGY STAR
LED PLDE/10-4.5W/830/G/4P	220 - 240V	4.5W	G24q	3000K	360°	AC	580lm	E
LED PLDE/10-4.5W/840/G/4P	220 - 240V	4.5W	G24q	4000K	360°	AC	605lm	E
LED PLDE/10-4.5W/865/G/4P	220 - 240V	4.5W	G24q	6500K	360°	AC	630lm	D
LED PLDE/13-5W/830/G/4P	220 - 240V	5W	G24q	3000K	360°	AC	680lm	D
LED PLDE/13-5W/840/G/4P	220 - 240V	5W	G24q	4000K	360°	AC	705lm	D
LED PLDE/13-5W/865/G/4P	220 - 240V	5W	G24q	6500K	360°	AC	730lm	D
LED PLDE/18-6W/AC/830/G/4P	220 - 240V	6W	G24q	3000K	360°	AC	800lm	E
LED PLDE/18-6W/AC/840/G/4P	220 - 240V	6W	G24q	4000K	360°	AC	835lm	D
LED PLDE/18-6W/AC/865/G/4P	220 - 240V	6W	G24q	6500K	360°	AC	870lm	D
LED PLDE/26-9W/AC/830/G/4P	220 - 240V	9W	G24q	3000K	360°	AC	1250lm	D
LED PLDE/26-9W/AC/840/G/4P	220 - 240V	9W	G24q	4000K	360°	AC	1300lm	D
LED PLDE/26-9W/AC/865/G/4P	220 - 240V	9W	G24q	6500K	360°	AC	1350lm	D

New installation / ECG rewiring AC Input



Direct 220 - 240V AC input. Integral LED driver
This LED PLD/E is not suitable for ECG Circuit. Please bypass the ECG for AC connection