


LED T5 AC





Features

- Energy saving with low power consumption
- Smooth operation even at low temperatures
- No mercury and hazardous substances
- Full glass body
- Voltage: 220-240Vac, 50/60Hz, Power Factor: 0.5
- Good color rendition, $R_a \geq 80$




EUROPE

TUBE



Model	Voltage	Wattage	Color Temp	Beam Angle	Type	Length L1 / L2	Efficacy	Lumen	
LED F8T5/AC/830/600	220 - 240V	8W	3000K	270°	AC	549mm / 563mm	115lm/W	920lm	E
LED F8T5/AC/840/600	220 - 240V	8W	4000K	270°	AC	549mm / 563mm	118lm/W	940lm	E
LED F8T5/AC/865/600	220 - 240V	8W	6500K	270°	AC	549mm / 563mm	120lm/W	960lm	E
LED F12T5/AC/830/900	220 - 240V	12W	3000K	270°	AC	849mm / 863mm	115lm/W	1380lm	E
LED F12T5/AC/840/900	220 - 240V	12W	4000K	270°	AC	849mm / 863mm	118lm/W	1410lm	E
LED F12T5/AC/865/900	220 - 240V	12W	6500K	270°	AC	849mm / 863mm	120lm/W	1440lm	E
LED F16T5/AC/830/1200	220 - 240V	16W	3000K	270°	AC	1149mm / 1163mm	115lm/W	1840lm	E
LED F16T5/AC/840/1200	220 - 240V	16W	4000K	270°	AC	1149mm / 1163mm	118lm/W	1880lm	E
LED F16T5/AC/865/1200	220 - 240V	16W	6500K	270°	AC	1149mm / 1163mm	120lm/W	1920lm	E
LED F20T5/AC/830/1500	220 - 240V	20W	3000K	270°	AC	1449mm / 1463mm	115lm/W	2300lm	E
LED F20T5/AC/840/1500	220 - 240V	20W	4000K	270°	AC	1449mm / 1463mm	118lm/W	2350lm	E
LED F20T5/AC/865/1500	220 - 240V	20W	6500K	270°	AC	1449mm / 1463mm	120lm/W	2400lm	E



Direct 220 - 240Vac input. Integral LED driver

