

LED 支架 NL181A-184A
12W/24W/36W

标准



应用



家居



办公室



购物中心



旅馆



超市



餐厅



停车场



学校



仓库



工厂



医院



艺术馆



博物馆



机场



铁路

技术参数

电参数

额定功率 [W]

12W / 24W / 36W

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com

额定电压 [V/Hz]	110–130Vac, 50/60Hz
功率因数 @120V	0.9
输入电流 [mA] @120V	111 / 222 / 333
LED	SMD
产品型号	
NL181A-12W/840	12W
NL182A-24W/840	24W
NL183A-36W/840	36W
NL184A-24W/840	24W
光通量 [lm]	
12W	800lm @4000K
24W	1600lm @4000K
36W	2400lm @4000K
24W	2100lm @4000K
光效性能	
色容差	<6
预计每年能源支出 [\$USD]	1.45 / 2.89 / 4.34
光效 [lm/W]	67–88
显色指数 [Ra]	≥85
色效维持 [hr]	>6000
光度分布 [°]	120
寿命 [yrs] (每日使用3小时)	46
6000小时后, 光通维持率	>0.8
开关测试	>15,000 cycles
启动时间 [S]	<0.5
LED 失效率	<5%
尺寸和物料	
长度 L [in]	12.13 / 22.76 / 46.3 / 46.5
宽度 W [in]	1.57 / 1.57 / 1.57 / 1.5
高度 H [in]	1.73 / 1.73 / 1.73 / 1.87
物料	Steel and PC
标准	
ANSI	UL8750, UL1993, UL1598, C82.77–2002, C78.377–2008
汞含量 [mg]	0.0
其他	
调光 [Y/N]	N
工作温度	–20° C ~ 50° C
存储温度	–10° C ~ 30° C