


LED 天花灯 ND251E-253E 12W/18W/24W



图表

尺寸:



标准





IP20



应用









居 购物中心

旅馆


超市

餐厅

++++	
技术参数	
电参数	1.011 / 1.011 / 0.411
额定功率 [W]	12W / 18W / 24W
额定电压 [V/Hz]	220-240V, 50/60Hz
功率因数 @230V	0.5
输入电流 [mA] @230V	104 / 157 / 209
LED	COB
产品型号	
ND251E-12W/8XX	12W
ND252E-18W/8XX	18W
ND253E-24W/8XX	24W
光通量 [lm]	
12W	9601m @3000K
	9801m @4000K
	10001m @6500K
18W	13001m @3000K
	1380lm @4000K
	1450lm @6500K
24W	1750lm @3000K
	1800lm @4000K
	1850lm @6500K
光效性能	
	<6
光效 [lm/W]	72–83
	≥80
	15 / 24 / 38
额定寿命, Ta@25° C [hrs]	25,000
6000小时后, 灯残存率	>0.9
6000小时后,光通维持率	>0.8
	>15,000
	<0.5
	<2
1000小时后, 失效率	<5%
尺寸和物料	
直径 D [mm]	70
高度 H [mm]	103 / 118 / 138
物料	Body: Die-cast aluminium with Black finish
	Diffuser: Frosted PMMA, UV protected
标准	
CE-LVD	EN60598-1, EN60598-2-1
52 2.5	1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1

佑昌灯光器材有限公司

电话: (852) 2511 0022 传真: (852) 2511 0082 网址: www.prosperitylamps.com 电子邮件: info@prosperitylamps.com



日期: 2025-11-29 页数 3/3



CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
汞含量 [mg]	0.0
电器保护等级	I
其他	
调光 [Y/N]	N
工作温度	-10° C ~ 40° C
存储温度	-20° C ~ 60° C